

Machine foot HXJCFE- HEX150(s)-HXEH56200

ARTICLE NUMBER 2000191



Type HXJEHEX + HXJCFEHEX

The design and patent protected seismic HXJEHEX + HXJCFE-HEX levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact design
- Can be adjusted via hex at the top of the spindle
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

Technical specifications

Antislip	No	
Drawing no.	NGI 155935	
Footplate diameter	150 mm	5.91"
Footplate shape	Round	
Height adjustment	131 mm	5.16"
Height max.	216 mm	8.50"
Height min.	85 mm	3.35"
Height total	285 mm	11.22"
Mounting holes	4 Pieces	
Nom. Load	140000 N	
Nom. pull	17000 N	
Sleeve diameter	56 mm	2.20"
Sleeve length	55 mm	2.17"
Spindle length	200 mm	7.87"
Thread diameter	56 mm	2.20"
Thread length	200 mm	7.87"
Thread size	M56x5.5	
Thread standard	Metric C	

Technical specifications

