

# Machine foot HXJCFE- HEX150(s)-HXEH30150

ARTICLE NUMBER 2000183



## Type HXJEHEX + HXJCFEHEX

The design and patent protected seismic HXJEHEX + HXJCFE-HEX leveling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact design
- Can be adjusted via hex at the top of the spindle
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

## Technical specifications

|                    |            |       |
|--------------------|------------|-------|
| Antislip           | No         |       |
| Drawing no.        | NGI 155921 |       |
| Footplate diameter | 150 mm     | 5.91" |
| Footplate shape    | Round      |       |
| Height adjustment  | 116 mm     | 4.57" |
| Height max.        | 196 mm     | 7.72" |
| Height min.        | 80 mm      | 3.15" |
| Height total       | 235 mm     | 9.25" |
| Mounting holes     | 4 Pieces   |       |
| Nom. Load          | 60000 N    |       |
| Nom. pull          | 17000 N    |       |
| Sleeve diameter    | 30 mm      | 1.18" |
| Sleeve length      | 55 mm      | 2.17" |
| Spindle length     | 155 mm     | 6.10" |
| Thread diameter    | 30 mm      | 1.18" |
| Thread length      | 155 mm     | 6.10" |
| Thread size        | M30        |       |
| Thread standard    | Metric C   |       |

## Technical specifications

