

# Machine foot HXJCFE- HEX300(I)-HXEH72310

ARTICLE NUMBER 2000208



## Type HXJEHEX + HXJCFEHEX

The design and patent protected seismic HXJEHEX + HXJCFE-HEX leveling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact design
- Can be adjusted via hex at the top of the spindle
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

## Technical specifications

|                    |            |        |
|--------------------|------------|--------|
| Antislip           | No         |        |
| Drawing no.        | NGI 155949 |        |
| Footplate diameter | 300 mm     | 11.81" |
| Footplate shape    | Round      |        |
| Height adjustment  | 223 mm     | 8.78"  |
| Height max.        | 355 mm     | 13.98" |
| Height min.        | 132 mm     | 5.20"  |
| Height total       | 445 mm     | 17.52" |
| Mounting holes     | 4 Pieces   |        |
| Nom. Load          | 327000 N   |        |
| Nom. pull          | 39000 N    |        |
| Sleeve diameter    | 72 mm      | 2.83"  |
| Sleeve length      | 55 mm      | 2.17"  |
| Spindle length     | 313 mm     | 12.32" |
| Thread diameter    | 72 mm      | 2.83"  |
| Thread length      | 313 mm     | 12.32" |
| Thread size        | M72x6.0    |        |
| Thread standard    | Metric C   |        |

## Technical specifications

