

# Machine foot HXJCFE- HEX300(I)-HXEH90250

ARTICLE NUMBER 2000211



## Type HXJEHEX + HXJCFEHEX

The design and patent protected seismic HXJEHEX + HXJCFE-HEX leveling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact design
- Can be adjusted via hex at the top of the spindle
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

## Technical specifications

Antislip	No	
Drawing no.	NGI 155654	
Footplate diameter	300 mm	11.81"
Footplate shape	Round	
Height adjustment	143 mm	5.63"
Height max.	275 mm	10.83"
Height min.	132 mm	5.20"
Height total	387 mm	15.24"
Mounting holes	4 Pieces	
Net weight	33695 g	
Nom. load	432000 N	97117.46lbs
Nom. pull	39000 N	8767.55lbs
Sleeve diameter	90 mm	3.54"
Sleeve length	55 mm	2.17"
Spindle length	255 mm	10.04"
Thread diameter	90 mm	3.54"
Thread length	255 mm	10.04"
Thread size	M90x6.00	
Thread standard	Metric C	

## Technical specifications

