

Machine foot HXJCFE- HEX300(I)-HXEH64200

ARTICLE NUMBER 2000205



Type HXJEHEX + HXJCFEHEX

The design and patent protected seismic HXJEHEX + HXJCFE-HEX levelling foot is the optimal choice for machinery, equipment, tanks and vessels located in areas subject to earthquakes.

- Simple and fast installation with height-adjustable compact design
- Can be adjusted via hex at the top of the spindle
- Movable set-up - no concrete molding required
- Total seismic stability through bolted fixation and patented locking mechanism
- Verified through Finite Element Analysis (FEA) and calculated according to New Zealand seismic standard (NZS 4219)
- Seismic anchors chosen and approved by our experienced partner Hilti
- Stainless steel AISI 304/A2, 1.4301. Optional AISI 316/A4, 1.4401

Technical specifications

Antislip	No	
Drawing no.	NGI 155943	
Footplate diameter	300 mm	11.81"
Footplate shape	Round	
Height adjustment	122 mm	4.80"
Height max.	243 mm	9.57"
Height min.	121 mm	4.76"
Height total	326 mm	12.83"
Mounting holes	4 Pieces	
Nom. Load	236000 N	
Nom. pull	39000 N	
Sleeve diameter	64 mm	2.52"
Sleeve length	55 mm	2.17"
Spindle length	205 mm	8.07"
Thread diameter	64 mm	2.52"
Thread length	205 mm	8.07"
Thread size	M64x6.0	
Thread standard	Metric C	

Technical specifications

